

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:
A61K 7/16
A1
(11) International Publication Number: WO 00/69401
(43) International Publication Date: 23 November 2000 (23.11.00)

(21) International Application Number: PCT/US00/12972
(22) International Filing Date: 11 May 2000 (11.05.00)

(30) Priority Data: 09/312,287 14 May 1999 (14.05.99) US

(71) Applicant: COLGATE-PALMOLIVE COMPANY [US/US]; 300 Park Avenue, New York, NY 10022 (US).

(72) Inventors: YAMANE, Odete, T.; Rua Biobedas, 15 Apto., CEP-63 Saude S. Paulo, SP (BR). CORREA, Fernanda, C., G.; Rua Joaquim Guarani, CEP-0452 Brooklyn S. Paulo, SP (BR). MORISITA, Rosangela, Takako; Av. do Cafe, 54-Apto., CEP-151 Jabaquara S. Paulo, SP (BR).

(74) Agents: SHAPIRO, Paul et al.; Colgate-Palmolive Company, 909 River Road, P.O. Box 1343, Piscataway, NJ 08855-1343 (US). (81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD FOR THE MANUFACTURE OF TOOTHPASTE

(57) Abstract

A method is disclosed for the manufacture of a toothpaste containing an ingredient mixture of a calcium carbonate abrasive, a thickener and an aqueous humectant wherein there is sequentially added the calcium carbonate abrasive dispersed in a high solids aqueous dispersion containing 50 to 80% by weight calcium carbonate to the aqueous humectant and thereafter adding the binder and binding the ingredients before any further ingredients are added to the mixture to produce the toothpaste.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ	Senegal Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HÜ	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	ΙL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand	2	Zimbabwe
CM	Carneroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		· ·
EE	Estonia	LR	Liberia	SG	Singapore		
					-···o-r		

METHOD FOR THE MANUFACTURE OF TOOTHPASTE

BACKGROUND OF THE INVENTION

5

10

1. Field of the Invention

This invention relates to the manufacture of toothpastes and more particularly to a method of manufacturing a toothpaste which contains an abrasive system comprised at least in part of calcium carbonate.

2. The Prior Art

Dentifrices, such as toothpaste are generally extrudable pastes containing insoluble

abrasives that aid in the removal of plaque, stains and other deposits from the teeth and help
to polish them. Toothpaste compositions contain a variety of ingredients, the major types of
ingredients generally being abrasive particulates,, a thickening agent, a liquid vehicle and
surfactant. Other ingredients include flavoring agents and various other constituents for
cosmetic, therapeutic or aesthetic effects.

20

25

Abrasives suitable for use in toothpaste compositions are generally finely divided, water-insoluble powdered materials such as silica, dicalcium phosphate dihydrate, calcium carbonate or calcined alumina. The toothpaste generally consists of a suspension of the abrasive in an aqueous humectant liquid phase. In order to hold the solid and liquid ingredients in the form of a stable paste with desirable rheological properties, the toothpaste invariably also includes a thickener or binder. A large number of different thickeners are known to the art and include, carboxymethylcellulose, xanthan gum, guar gum, carrageenan and mixtures thereof as thickener systems for toothpaste.

When preparing toothpastes, the toothpaste manufacturer encounters certain difficulties using abrasive powders and thickener systems to make a consumer acceptable toothpaste. For example, handling problems are encountered with the powdered abrasive where the particulate solids represent 10-60% by weight of the total toothpaste product and wherein the powders are low in bulk density which causes powder loss on debagging and during addition to the ingredient mixing tank. Also, upon the addition of the abrasive powder to the other ingredients in the mixing tank, there is a strong tendency towards lumping when combined with the water and humectant liquids present therein

10

15

20

25

SUMMARY OF THE INVENTION

In accordance with the present invention, a method is provided for the rapid, lump-free addition of calcium carbonate abrasive powders used for the preparation of toothpaste compositions wherein the powders constitute a major portion of the product, which method is a marked simplification of earlier powder addition techniques and comprises charging the water and humectant vehicle ingredients of the toothpaste to a mixing tank, introducing the abrasive calcium carbonate powder as a high solids slurry, in the order of 50-80% by weight solids, directly into the liquid vehicle and thereafter subjecting the ingredient mixture to homogenization by intimate mixing followed sequentially by the addition of a thickener and additional water to adjust the rheology of the paste product to the desired extrudible consistency.

It is critical to the practice of the present invention that the thickener ingredient be added to the water/humectant liquid vehicle after the addition of the abrasive slurry as the reverse sequence will cause a viscous gel to form which is difficult to subject to further processing. It is further critical to the method of the present invention that any further water addition to adjust the toothpaste rheology be made after the addition of the thickener so that a lump-free, smooth textured toothpaste product is obtained.

In a preferred embodiment of the invention, an essentially smooth, lump-free dentifrice paste is obtained in accordance with the above described method by first introducing a liquid vehicle comprised of a humectant such as glycerol, liquefied sorbitol (generally a 70% aqueous solution) or other liquid polyols, followed in sequence by the addition of the calcium carbonate abrasive slurry, a thickener such as carboxymethylcellulose and then water to a mixing tank and thereafter subjecting the ingredients to a continuous vacuum and intimate mixing between each sequence to prepare a homogeneous paste mixture.

10

15

20

25

30

5

The liquid vehicle of the dentifrice paste products made in accordance with the present invention is generally a humectant/water mixture, and will generally be present in the final paste product in the range of from about 10 to 85% by weight, with from 30-70% being a preferred range for toothpastes. Humectants used in dentifrice formulations are well known in the art and include glycerine, sorbitol, propylene glycol, polyethylene glycol, mannitol, polypropylene glycols, and mixtures thereof.

Stable aqueous calcium carbonate slurries used in the method of the present invention generally contain about 50 to about 80% by weight calcium carbonate. Such slurry materials are available commercially and are widely used in the paper making industry; calcium carbonate being a pigment which is excellent in whiteness and has affinity for ink, gloss and printability.

Inorganic dispersants which may be used to stabilize the calcium carbonate slurry include such condensed phosphates as pyrophosphates, tripolyphosphates, trimetaphosphates, tetrametaphosphates, and hexametaphosphates, zinc salts and silicates. Organic dispersants, include polycarboxylates such as polyacrylates, polymethacrylates, and polymaleates and polyvinyl alcohol. Such dispersants are known to the art, for example, US 4,818,783 discloses dispersing calcium carbonate in an aqueous medium containing as the dispersant (1) 0.1 to 2 parts by weight of (a) a carboxyl group-containing water-soluble polymer possessing a number average molecular weight in the range of 2,000 to 80,000 and (b) a water soluble

condensed phosphate and (2) 0.03 to 1 part by weight of a water soluble anionic modified polyvinyl alcohol respectively based on 100 parts by weight of the calcium carbonate.

The content of calcium carbonate abrasive in the final paste product will range from about 20 to about 75% and preferably about 30 to about 60% by weight.

Thickeners that can be used in accordance with the method of the present invention preferably include the natural and synthetic gums and gum-like materials, desirably carboxyl methyl cellulose sodium carboxymethylcellulose, hydroxyethylcarboxymethylcellulose, carrageenin, gum tragacanth, xanthan gum, guar gum, alginates, bentonite and other natural clays and synthetic inorganic clays. The gums are hydratable or gelled with water or alkanols, especially with polyhydric alcohols such as glycerol and sorbitol.

The proportions of thickeners present in the toothpaste product of the present invention will generally be in the range of from 0. 1-to about 5% by weight of the final product and in the case of synthetic gums such as sodium carboxymethylcellulose, the range will preferably be from about 0.1 to 3%.

Inorganic thickening agents suitable for use in the present invention include colloidal silicas having bodying properties, such as the aerogels Syloid 244 and 266 (available from W. R. Grace Company), Aerosil (available from DeGussa Co.) and pyrogenic silicas sold under the tradename Cab-O-Sils (available from Cabot Corporation). Tixosil 333 and Tixosil 43B (available from Rhodia Ltda.), Zeodent 165 (available from J.M. Huber Corporation).

In the manufacture of the toothpaste in accordance with the method of the present invention, mixing of the ingredients is accomplished in mixing vessels conventionally used and equipped for the manufacture of toothpaste. The ingredients may be charged to mixer at an elevated temperatures for example 45to 70°C, but is preferably performed at room temperature to save heating and cooling times.

25

10

20

Once the homogeneous paste containing the aqueous humectant, abrasive and thickener is prepared, which can generally be referred to as a base paste, various other classes of ingredients may be added to finalize the toothpaste product, which additional ingredients generally include surfactants, silica aerogels or other colloidal silicas, therapeutic agents, preservatives and flavoring agents or other ingredients that will finalize the desired toothpaste product.

5

10

25

30

Examples of surfactants useful in the toothpastes prepared in accordance with the method of the present invention include anionic surfactants such as sodium alkylsulfates (sodium laurylsulfate, sodium myristylsulfate), sodium N-acylsarcosinates (sodium N-lauroylsarcosinate, sodium N-myristoylsarcosinate, N-acylglutamic acid salts (sodium N-palmitoylglutamate, etc.), and sulfosuccinic acid surfactants (polyoxyethylene alkyl disodium sulfosuccinate, dialkyl sodium sulfosuccinate).

Examples of nonionic surfactants usable in the method of the present invention include sugar fatty acid esters (sucrose fatty acid ester, maltose fatty acid ester, lactose fatty acid ester, etc.), polyoxyethylene alkyl ethers, polyoxyethylene sorbitan fatty acid esters (polyoxyethylene sorbitan mono laurate, polyoxyethylene sorbitan monostearate, etc.), polyoxyethylene fatty acid esters (polyoxyethylene-hardened castor oil, etc.), sorbitan fatty acid esters, fatty acid monoglycerides and polyoxyethylene/polyoxypropylene block copolymers.

Examples of amphoteric surfactants usable herein include
N-alkyldiaminoethylglycine (N-lauryldiaminoethylglycine, N-myristyldiethylglycine,
etc.), N-alkyl-N-carboxymethylammonium betaine, 2-alkyl-1-hydroxyethylimidazoline
betaine sodium and lauryldimethylaminoacetic acid betaine.

Either one of the above described surfactants or a mixture of two or more thereof may be used to prepare the toothpaste composition of the present invention at a concentration ranging from 0.1 to 10% by weight based on the whole composition.

The toothpaste compositions prepared in accordance with the process of the present invention may also contain flavors such as menthol, arvensis mint oil, synthetic mint flavors, carvone, eugenol, methyleugenol, methyl salicylate, methyl eugenol, thymol, anethole, limonene, ocimene, n-decyl alcohol, citronellol, .alpha.-terpineol, linalol, ethyllinalol, vanillin, thyme, nutmeg, spearmint oil, peppermint oil, lemon oil, orange oil, sage oil, rosemary oil, cinnamon oil, winter green oil, clove oil and eucalyptus oil. Either one of these flavors or a mixture of two or more thereof may be used. The content thereof ranges from 0.1 to 5% by weight, preferably from 0.5 to 2% by weight, based on the whole composition.

The toothpaste compositions of the present invention may also contain sweeteners such as saccharin sodium, acesulfame potassium, glycyrrhizin, perillartine, thaumatin, aspartylphenylalanyl methyl ester and xylitol. The content of the sweeteners ranges from 0.01 to 1% by weight, preferably from 0.05 to 0.5% by weight, based on the whole composition.

The toothpaste composition prepared in accordance with the method of the present invention may furthermore contain therapeutic ingredients such as water-insoluble noncationic antibacterial agents such as triclosan, Vitamin E analogs (dl-.alpha.-tocopherol acetate, tocopherol succinate, tocopherol nicotinate, etc.), Vitamin A (retinol, alpha carotene, beta carotene), Vitamin B (B1-thyamin, B2-riboflavine, B3-niacine, B5-pantothenic acid, B6-pirydoxine, B7-biotine, B8/B9/Bc-folic acid, B12-cianocobalamine), Vitamin C (ascorbic acid, sodium ascorbate), cationic antibacterial agents (chlorhexidine hydrochloride, cetylpyridinium chloride), enzymes (dextranase, amylase, protease, mutanase, lysozyme), herbal extracts/oils (chamomile, myrrh, eugenol, tea tree oil, sage oil, mallow, eucalyptus, melissa, pomegranade, apricot, millefolium extract, tangerine extract), natural ingredients (algae, propolis), anticavity alkali metal agents and monofluorophosphates (sodium monofluorophosphate, potassium monofluorophosphate, etc.), fluorides (sodium fluoride, stannous fluoride, etc.), whitening agents (aluminum oxide, calcium peroxide), debriding agent (sodium bicarbonate), astringent salts (such as zinc), chlorophyll, and preservatives

such as methyl paraben, tooth desensitizing agents such as potassium and stronthium salts, condensed antitartar phosphates such as sodium and potassium tetrapyrophosphate, pigments (Blue 15-CI74160, Green 7-CI74260, Red 4-CI12085, Yellow 115 CI47005:1), dyes (Red 40 CI16035,Red 33 CI17200, Red 3 CI45430, Carmine 5 CI75470, Blue 1 CI42090, Yellow 5 CI19140, Yellow 10 CI47005) Mica and Speckles. Use can be made of either one of these ingredients or a mixture of two or more thereof in amounts ranging from 0.001 to abut 15% by weight of the toothpaste.

10

5

The following Example is illustrative of the invention. All percentages are by weight.

Example

A toothpaste was made according to the following formula:

15

	% Weight
Sorbitol	20.00
Carboxymethylcellulose (CMC)	1.20
Irradiated water	5.020
Calcium carbonate (65% by weight slurry)	63.080
Sodium saccharin	0.200
Methylparaben	0.100
Ethyl alcohol	1.500
Sodium silicate	1.000
Sodium monofluorophosphate	1.140
Sodium lauryl sulfate (SLS) 29% solution	5.600
Flavor	1.160

The toothpaste was made in Frima Mixer toothpaste mixer. Mixing was carried out under vacuum of 600-680 mm Hg. The mixing steps were as follows:

- Stage 1 The sorbitol was put in the mixer.
- Stage 2 Half the water content was added to the mixer.
- Stage 3 The calcium carbonate slurry, containing 65% by weight calcium carbonate,
 available from Quimbarra Company, Rio de Janeiro, Brazil stabilized with sodium silicate and sodium hexametaphosphate dispersants was drawn into the mixer. Mixing took place for about 1 minute to prepare a homogeneous dispersion.
 - Stage 4 A suspension of CMC thickener and the preservative, methyl paraben in ethanol
 prepared in a separate mixing vessel, was added to the mixer and mixed for 15 minutes,
 with a mixing anchor speed of 22 rpm.
 - Stage 5 A solution of sodium saccharin and sodium monofluorophosphate was prepared with the remainder of the water in a separate vessel and added to the mixer and mixed for 2 minutes to produce a smooth cream.
 - Stage 6 Sodium silicate was added to the mixer.
- Stage 7 The flavor was added to the mixer and mixed for 2 minutes.
 - Stage 8 SLS was added and mixed for 20 minutes.

The toothpaste prepared in accordance with the sequential steps described above had a satisfactory smooth texture and acceptable appearance. A comparative toothpaste, which was not made by the method of this invention, that is Stage 4, was performed before Stage 3 or Stage 5 was performed before Stage 4, resulted in a toothpaste product that had a rough granular texture. The coarse texture of the toothpaste ribbon, especially noticeable when spread with the finger, meant that the product was of poor quality. The toothpaste ribbon lacked the uniformly smooth texture required of an acceptable commercial product.

25

20

10

CLAIMS

What is claimed is:

5

10

- 1. A method for making a toothpaste containing an ingredient mixture of a calcium carbonate abrasive, a thickener and an aqueous humectant which comprises sequentially adding the calcium carbonate abrasive dispersed in a high solids aqueous dispersion containing about 50 to about 80% by weight calcium carbonate to the aqueous humectant and thereafter adding the thickener and mixing the ingredients before any further ingredients are added to the mixture to produce the toothpaste.
- 2. The method of claim 1 wherein the thickener is carboxymethyl cellulose.
- 15 3. The method of claim 1 wherein the humectant is sorbitol.
 - 4. The method of claim 1 wherein the content of calcium carbonate in the toothpaste ranges from about 20 to about 70% by weight.
- 5. The method of claim 1 wherein the thickener is present in the toothpaste at a concentration of about 0.1 to about 5% by weight.

INTERNATIONAL SEARCH REPORT

inter onal Application No PCT/US 00/12972

<u> </u>			1 11, 00 00, 123,2		
A. CLASS IPC 7	SFICATION OF SUBJECT MATTER A61K7/16				
According t	to International Patent Classification (IPC) or to both national da	assification and IPC			
	S SEARCHED				
IPC 7					
	ation searched other than minimum documentation to the extent				
f	ata, PAJ, EPO-Internal, CHEM ABS D		,		
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT				
Category °	Citation of document, with indication, where appropriate, of the	he relevant passages	Relevant to claim No.		
А	GB 1 599 689 A (COLGATE-PALMOL 7 October 1981 (1981-10-07) the whole document	IVE)	1-5		
Α	EP 0 097 476 A (PROCTER & GAMB 4 January 1984 (1984-01-04) example 1	1–5			
A	EP 0 565 401 A (COLGATE-PALMOL 13 October 1993 (1993-10-13) the whole document	1-5			
A	EP 0 190 762 A (BLENDAX-WERKE I SCHNEIDER) 13 August 1986 (1986 the whole document	1-5			
Furth	ner documents are listed in the continuation of box C.	X Patent family me	embers are listed in annex.		
^o Special cate	tegories of cited documents :	*T* later document publis	hed after the international filing date		
"A" documer conside "E" earlier do	ot in conflict with the application but the principle or theory underlying the r relevance; the claimed invention				
which is	ate nt which may throw doubts on priority claim(s) or s cited to establish the publication date of another or other special reason (as specified)	d novel or cannot be considered to step when the document is taken alone r relevance; the claimed invention			
"O" documer other me	d to involve an inventive step when the ad with one or more other such docu- tion being obvious to a person skilled				
later tha	nt published prior to the international filing date but an the priority date claimed	in the art. "&" document member of			
	ctual completion of the international search	,	Date of mailing of the international search report		
	October 2000	11/10/200	00		
Name and ma	ailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Fischer,	Authorized officer Fischer, J.P.		

Carried and the second of the

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter onal Application No PCT/US 00/12972

		1 101/03 00/123/2			
Patent document cited in search report	Publication date		Patent family member(s)	Publication date	
GB 1599689 A	07-10-1981	AR	218540 A	13-06-1980	
		AT	363602 B	25-08-1981	
		AT	347279 A	15-01-1981	
		AU	523563 B	05-08-1982	
		AU	4611179 A	29-11-1979	
1		BE	876425 A	17-09 - 1979	
ŀ		BR	7903126 A	11-12-1979	
ľ		CA	1118360 A	16-02-1982	
		CH	641955 A	30-03-1984	
		DE	2918132 A	29-11-1979	
		DK	178579 A,B	26-11-1979	
		FR IE	2426458 A 48240 B	21-12-1979 14-11-1984	
		IT	1116852 B	10-02-1986	
		JP	1449040 C	11-07-1988	
		JP	54157843 A	13-12-1979	
		JP	62056125 B	24-11-1987	
		MX	153894 A	11-02-1987	
		MY	10183 A	31-12-1983	
		MY	10283 A	31-12-1983	
		NL	7903191 A	27-11-1979	
		NO	791702 A,B,	27 - 11-1979	
		NZ	190071 A	16-03-1981	
		PH	15533 A	09-02-1983	
		PT	69497 A	01-05-1979	
İ		SE	444763 B	12-05-1986	
		SE	7902993 A	26-11-1979	
		ZA 	7901715 A	26-11-1980 	
EP 97476 A	04-01-1984	AT AT	46262 T 66587 T	15-09-1989 15-09-1991	
		AT	66588 T	15-09-1991	
		ÂŤ	60901 T	15-03-1991	
		CA	1233121 A	23-02-1988	
		DE	3380553 D	19-10-1989	
		DE	3382169 D	28-03-1991	
		DE	3382395 A	02-10-1991	
		DE	3382396 A	02-10-1991	
		EP	0297211 A	04-01-1989	
		EP	0297212 A	04-01-1989	
		EP	0297213 A	04-01-1989	
		EP	0319516 A	07-06-1989	
		EP EP	0345821 A	13-12-1989	
		FI	0395117 A 832275 A,B,	31-10-1990 23-12-1983	
		FI	88107 B	31-12-1992	
		GR	79211 A	22-10-1984	
		IE	56956 B	12-02-1992	
		ĬĒ	56957 B	12-02-1992	
		JP	6002657 B	12-01-1994	
		JP	59042311 A	08-03-1984	
		MX	156152 A	19-07-1988	
		PH	22221 A	28-06-1988	
		US	4806339 A	21-02-1989	
		US	4772461 A	20-09-1988	
		US	4885155 A	05-12-1989	
		110	4000104 4	12-03-1991	
		US	4999184 A		
		US	4515772 A	07-05-1985	

INTERNATIONAL SEARCH REPORT

information on patent family members .

Inte onal Application No PCT/US 00/12972

				101/00 00/12372		
Patent document cited in search report		Publication date		Patent family member(s)	Publication date	
EP 97476	Α		US	4590066 A	20-05-1986	
			US	4684518 A	04-08-1987	
EP 565401	Α '	13-10-1993	US	5236696 A	17-08-1993	
			AT	154512 T	15-07-1997	
			AU	3541793 A	30-09-1993	
			BG	61675 B	31-03-1998	
			BG	97579 A	31-03-1995	
			BR	9301305 A	05-10-1993	
			CN	1083700 A,B	16-03-1994	
			DE	69311616 D	24-07-1997	
į			GR	93100121 A,B	30-11-1993	
			HK	1007282 A	09-04-1999	
			JP	6009335 A	18-01-1994	
			MX	9301514 A	01-12-1993	
			PL	298264 A	07-03-1994	
			RO	112988 A	30 - 03-1998	
			TR	28582 A	22 - 10-1996	
			US	5320832 A	14-06-1994	
1			ZA	9301728 A	10-09-1994	
		~~~~~	ZW	3893 A	11-01-1993	
EP 190762	Α	13-08-1986	DE	3504178 A	14-08-1986	
			AT	74747 T	15-05-1992	
			CH	672065 A	31-10-1989	
			DE	3684794 A	21-05-1992	
			JP	2118055 C	06-12-1996	
			JP	8032619 B	29 <b>-</b> 03-1996	
			JP	61183215 A	15-08-1986	
			ZA	8600599 A	29-10-1986	
•						